

TECHNICAL DATA SHEET**QRR010908****Supplier****Starrsed Anti-foam**

Mechatronics Instruments B.V.
P.O. Box 225
1620 AE Hoorn
The Netherlands
Phone: +31 229 291 129
Fax: +31 229 241 534

Application

Starrsed Anti-foam is added to manually prepared Rinse solution to prevent foaming. This solution is used to clean the Westergren pipettes on the Starrsed III ESR analyzer. The product is not to be used on other Starrsed analyzers. The product is only to be used in a dilution, see the instrument manual for instructions.

Chemical/Physical data

Form:	Fluid.
Colour:	Colourless.
Smell:	Characteristic.
Melting temperature:	-16.3°C
Boiling temperature:	194.4°C
Flash point:	81°C
Ignition temperature:	270°C
Danger of explosion:	Product is not explosive.
Steam pressure at 20°C:	0.032 hPa
Density at 20°C:	0.82 g/cm ³
pH-value at 20°C:	Not available.
Solubility in / Miscibility with water:	0.3 g/l

The latest version of the Material Safety Data Sheet is available on the website www.rrmechatronics.com

Storage/Packaging

Store in cool, dry conditions in well sealed containers.
Starrsed Anti-foam is supplied in bottles of 10 ml.

Shelf life

After production: 4 years, but no longer than the expiry date.

After opening the packaging: Maximum of 3 month at advised temperature of 15 till 25°C.

Ecological information

Water hazard class (D) 1 (Self-assessment): Slightly hazardous for water.
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

Disposal

Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.